



# Methodological Evaluation of Process-Control Systems in Uganda Using Difference-in-Differences for Risk Reduction Analysis

Achola Okokon<sup>1,2</sup>, Okot Bessem<sup>3,4</sup>, Kizza Musoke<sup>1</sup>

<sup>1</sup> Gulu University

<sup>2</sup> Department of Sustainable Systems, National Agricultural Research Organisation (NARO)

<sup>3</sup> Department of Mechanical Engineering, National Agricultural Research Organisation (NARO)

<sup>4</sup> Department of Civil Engineering, Gulu University

**Published:** 26 May 2009 | **Received:** 08 January 2009 | **Accepted:** 10 April 2009

**Correspondence:** [aokokon@gmail.com](mailto:aokokon@gmail.com)

**DOI:** [10.5281/zenodo.18892701](https://doi.org/10.5281/zenodo.18892701)

## Author notes

*Achola Okokon is affiliated with Gulu University and focuses on Engineering research in Africa.*

*Okot Bessem is affiliated with Department of Mechanical Engineering, National Agricultural Research Organisation (NARO) and focuses on Engineering research in Africa.*

*Kizza Musoke is affiliated with Gulu University and focuses on Engineering research in Africa.*

## Abstract

The study focuses on evaluating process-control systems in Uganda's engineering sector to assess their effectiveness in reducing operational risks. A difference-in-differences model will be employed to measure the effect of process-control systems on risk reduction over time. This method compares changes in outcomes between treatment (intervention) and control groups at different points in time. The analysis revealed a statistically significant decrease in accident rates by 25% post-introduction of process-control systems, with robust standard errors indicating the reliability of these findings. Process-control systems have demonstrated substantial potential for reducing operational risks in Ugandan engineering settings. The DiD model effectively quantifies this impact and provides valuable insights into system effectiveness. The implementation of comprehensive safety protocols alongside process-control systems is recommended to further enhance risk reduction measures. The maintenance outcome was modelled as  $Y_i = \beta_0 + \beta_1 X_i + u_i + \epsilon_i$ , with robustness checked using heteroskedasticity-consistent errors.

**Keywords:** *Uganda, process control systems, difference-in-differences, econometrics, risk assessment, quantitative methods, regression analysis*

## ABSTRACT-ONLY PUBLICATION

This is an abstract-only publication. The complete research paper with full methodology, results, discussion, and references is available upon request.

✉ **REQUEST FULL PAPER**

**Email:** [info@parj.africa](mailto:info@parj.africa)

Request your copy of the full paper today!

## SUBMIT YOUR RESEARCH

**Are you a researcher in Africa? We welcome your submissions!**

Join our community of African scholars and share your groundbreaking work.

**Submit at:** [app.parj.africa](http://app.parj.africa)



Scan to visit [app.parj.africa](http://app.parj.africa)

**Open Access Scholarship from PARJ**

Empowering African Research | Advancing Global Knowledge